

Some Wireless Thermostats



Model: ST7RF

Transmitter:

- 2 x AA size battery
- 6 Time & 6 Temp. per day
- 7 Day programmable
- 868Mhz for more stable communication
- EL back light
- Manual override mode

Receiver:

- AUTO/MANUAL Switch
- LED system Indicator
- Contact rating: 8(2)A 230VAC Max



Model: ST3RF

Transmitter:

- non-programmable
- POWER: 2 x AA size battery
- Temperature range: 5°C-35°C in 0.5°C
- Control temp range: 10°C-30°C in 0.5°C
- 868Mhz for more stable communication
- ON/OFF switch
- Bat-low indicator

Receiver:

- AUTO/MANUAL Switch
- LED system Indicator
- Contact rating: 8(2)A 230VAC Max



Model: ST23RF

Transmitter:

- non-programmable
- POWER: 2 x AAA size battery
- Temperature range: 5°C-35°C in 0.5°C
- Control temp range: 10°C-30°C in 0.5°C
- 868Mhz for more stable communication
- HEAT/OFF/COOL switch
- Bat-low indicator

Receiver:

- AUTO/MANUAL Switch
- LED system Indicator
- Contact rating: 8(2)A 230VAC Max



Model: ST27RF

Transmitter:

- 7 Day programmable
- 6 Time & 6 Temp. per day
- 2 x AAA size battery
- Keypad lockout
- HEAT/COOL mode switch
- 868Mhz for more stable communication

Receiver:

- AUTO/MANUAL Switch
- LED system Indicator
- Contact rating: 8(2)A 230VAC Max



Model: ST2305RF

Transmitter:

- non-programmable
- POWER: 2 x AAA size battery
- Temperature range: 5°C-35°C in 0.5°C
- Control temp range: 10°C-30°C in 0.5°C
- 868Mhz for more stable communication
- HEAT/OFF/COOL switch
- Bat-low indicator

Receiver:

- AUTO/MANUAL Switch
- LED system Indicator
- Contact rating: 8(2)A 230VAC Max



Model: ST28RF

Transmitter:

- 7 Day programmable
- 48 Time & 2 Temp. per day
- 2 x AAA size battery
- Keypad lockout
- HEAT/COOL mode switch
- 868Mhz for more stable communication

Receiver:

- AUTO/MANUAL Switch
- LED system Indicator
- Contact rating: 8(2)A 230VAC Max

Ocean Controls Limited

Contact: Yolanda Li

Email: Sandy@ocstat.com

Wechat: +86 13829231275