








New Style Digital Room Thermostat

	<p>Model: ST2305</p> <ul style="list-style-type: none"> ● non-programmable ● POWER: 2 x AAA size battery ● Temperature range: 3°C-37°C in 0.1°C ● Control temp range: 5°C-35°C in 0.5°C ● HEAT/OFF/COOL mode switch ● Bat-low indicator ● 2 x AAA size battery ● Contact rating: 8(2)A 230VAC Max 	
	<p>Model: ST2401</p> <ul style="list-style-type: none"> ● non-programmable ● 2 x AAA size battery ● Temperature range: 0°C-40°C in 0.1°C ● Control temp range: 5°C-35°C in 0.5°C ● HEAT/OFF/COOL mode switch ● Bat-low indicator ● Contact rating: 8(2)A 230VAC Max 	<p>Model: ST2401RF</p> <p>Transmitter:</p> <ul style="list-style-type: none"> ● non-programmable ● POWER: 2 x AAA size battery ● Temperature range: 0°C-40°C in 0.1°C ● Control temp range: 5°C-35°C in 0.5°C ● 868Mhz for more stable communication ● HEAT/OFF/COOL switch ● Bat-low indicator <p>Receiver:</p> <ul style="list-style-type: none"> ● AUTO/MANUAL Switch ● LED system indicator ● Contact rating: 8(2)A 230VAC Max
	<p>Model: ST2402</p> <ul style="list-style-type: none"> ● 7 Day programmable ● 6 Time & 6 Temp. per day ● Manual override mode ● 2 x AAA size battery ● Contact rating: 8(2)A 230VAC Max ● Keypad lockout ● HEAT/COOL mode switch 	 <p>Model: ST2402RF</p> <p>Transmitter:</p> <ul style="list-style-type: none"> ● 7 Day programmable ● 6 Time & 6 Temp. per day ● 2 x AAA size battery ● Keypad lockout ● HEAT/COOL mode switch ● 868Mhz for more stable communication <p>Receiver:</p> <ul style="list-style-type: none"> ● AUTO/MANUAL Switch ● LED system indicator ● Contact rating: 8(2)A 230VAC Max
	<p>Model: ST2403</p> <ul style="list-style-type: none"> ● non-programmable ● 2 x AAA size battery ● Temperature range: 0°C-40°C in 0.1°C ● Control temp range: 5°C-35°C in 0.5°C ● HEAT/OFF/COOL mode switch ● Bat-low indicator ● Contact rating: 8(2)A 230VAC Max 	 <p>Model: ST2403RF</p> <p>Transmitter:</p> <ul style="list-style-type: none"> ● non-programmable ● POWER: 2 x AAA size battery ● Temperature range: 0°C-40°C in 0.1°C ● Control temp range: 5°C-35°C in 0.5°C ● 868Mhz for more stable communication ● HEAT/OFF/COOL switch ● Bat-low indicator <p>Receiver:</p> <ul style="list-style-type: none"> ● AUTO/MANUAL Switch ● LED system indicator ● Contact rating: 8(2)A 230VAC Max

Ocean Controls Limited

Contact: Yolanda Li

Email: Sandy@ocstat.com

We Chat: +86 13829231275